



## Product Description:

**GAZ-GR05** is multi-purpose extreme pressure grease made from lithium soap stock which imparts well high and low temperature characteristics and chemical stability. The load carrying additives system contains no lead or metals which are environmentally undesirable. The multi-purpose grease has high resistance to mechanical breakdown, excellent oxidation resistance, good rust protection, and excellent water “ wash-out” resistance, specially engineered for most of the manual or automatic centralized greasing system.

## Applications / Features:

- Provides high standards of long distance pump ability semi - fluid lubricants, most demanded in central systems tubing's.
- Advanced thickness provide complete surface protection
- High temperature resistance
- High pump ability through central system tubing
- Excellent Extreme Pressure (E. P.) protection
- Water “ wash - out ” resistant
- Anti - corrosion and oxidation
- HIGH TEMPERATURE PROPERTIES: It withstands long operation heat without fail.
- EXTREME PRESSURE PROTECTION: It contains superior E. P. (Extreme Pressure) additive to form a chemical bond on metal surface to protect heavily loaded and shock loaded bearings.
- ANTI-CORROSION: It contains chemical stability characteristics that keep away from rust, acidic and moisture attack.

## Typical Properties:

GRADE, NLGI	0	1
PENETRATION @ 77°F (ASTM WORKED)	355-385	315-335
DROPPING POINT, °F	345	350
COLOR	BLUE	BLUE
APPEARANCE	BUTTERY	BUTTERY
BASE OIL DATA;		
VISCOSITY:		
cST @ 40°C.	228	228
cST @ 100°C.	13.5	13.5