



Product Description:

GAZ - LM01 is a carefully balanced blend of high quality mineral oil combined with an effective emulsifier sulfur-chlorine anti-weld additive (E.P) and fatty oils for additional lubricity. Used as an emulsion, this product combines the good cooling characteristics of conventional water soluble oils with the high load carrying properties of active cutting oil. This permits its use where extreme pressure requirements and machining operations are too severe for conventional soluble oils. Additionally, this soluble oil is free of nitrates and phenols and foam inhibited to permit its use in high speed metal cutting operations.

Applications / Features:

- Used in cutting difficult to machine ferrous metals of all types.
- Recommended for use in surface broaching, pipe threading, plain threading and tapping of ferrous metals with machinability rating between 60-100. Recommended water to oil ratio 5:1 through 10:1 depending on machinability rating.
- Also used in milling, boring and turning, plain drilling, sawing and thread and form grinding of ferrous metals with machinability rating between 30-100. Recommended water to oil ratio 10:1 through 20:1, depending on machinability rating.
- Commonly used in plain grinding operations at ratios between 40:1 through 50:1.
- NOT suitable for cutting copper or its alloys as the E.P. properties will tarnish these metals. Can be used on aluminum.
- Excellent cooling ability
- High E.P. permits machining tough to cut steels.
- Smooth work finish provided by lubricity additive.
- Increased tool life through balanced additive package.
- Form stable emulsion even with hard water.

Typical Properties:

GRAVITY, °API	17.4
APPEARANCE	BRIGHT
COLOR, D-1500	BLUE
VISCOSITY:	
SUS @ 100°F	225
cST @ 40°C.	43.4
ACTIVE SULFUR, WT.%	0.5
CHLORINE, WT.%	2.0
COLD TEST @ 40°F	NO SEPARATION
EMULSIBILITY	PASS
EMULSION STABILITY	PASS
Ph, 5% in DI Water	7.0